

PLT240

LINKTower™
LED LIGHT TOWER

GENERAC

MAGNUM

SPECIFICATIONS

ELECTRICAL INLET / OUTLET

- 120V / 15A (NEMA 5-15R) Power Inlet
- 120V / 20A (NEMA L5-20P) Power Inlet
- 120V / 20A (NEMA 5-20R) GFCI Duplex Outlet

ELECTRICAL CONTROLS

- 15A / 20A power distribution switch
- 15A / 20A Main Breaker
- 5A Individual Light Switches

FLOODLIGHTS

- Four (4) 240W LED fixtures
 - 22,000 lumens each
 - 88,000 total lumens
- IP66 LED Modules with 50,000 hour life expectancy
- Individually adjustable light fixtures
- Aluminum / Poly construction housing
- Cabinet mounted LED drivers
- 30VDC mast cord and fixture
- Pinch Guard protects LED fixture cord routing



MAST

- Vertical mast; 16 ft. (4.9 m) 4-section with ground-adjustable light fixtures
- Dual handle manual winch for ease of deployment, enclosed tamper proof brake system
- Galvanized mast sections
- Self-retracting coiled mast cord
- Equipped with single lifting eye

CHASSIS

- 45 mph (72 kph) wind rating
- Steel frame with galvanized fork pockets
- (4) 1200 lb. (544 kg) leveling jacks
- Galvanized side outriggers lock in position for storage
- 3.5 x 8 in. (89 x 203 mm) all rubber tires
- 6 in. (152 mm) caster wheel with brake
- 24 in. (61 cm) track width

WEIGHT & DIMENSIONS

- Operating weight: 558 lb. (253 kg)
- Mast stowed: 54 x 31.5 x 77.5 in. (1.37 x .80 x 1.96 m)
- Mast and outriggers extended: 74 x 57 x 192 in. (1.88 x 1.45 x 4.88 m)

WARRANTY

2 Year / 2000 Hour on tower; 5 Year limited warranty on LED modules and drivers

CERTIFICATIONS

CSA Certified

For more information, consult the Owner's Manual at <http://www.generacmobileproducts.com/resources-tools/manuals>