# 10KPRO Portable Generator

## **Commercial / Residential**

10,000 Watt Running 12,500 Watt Starting Electric Start 680cc V-Twin

















## **Specifications**

10KPR0 10,000 **Running Watts: Starting Watts:** 12,500

> Alternator: <5% THD, All Copper

Voltage Regulation: Automatic/Remote Mounted

> Displacement: 680cc V-Twin

> > Type: OHV, 4 Stroke

Rated RPM: 3600

Lubrication: Pressure / Intercooled w/ Automotive Filter

Fuel Shut Off: Manual / Electronic

> Choke: Manual

Starting: Electric Only

Battery: Included, 21 Ahr

120 Volt Charging Port / Engine Charging **Battery Charging:** 

in Operation

**Engine Protection:** Low Oil Shutdown

**Emission Certifications:** EPA / CARB

Other Certifications:

**Receptacle Protection:** (1) 42 Amp Main Toggle

(1) 30 Amp Toggle

(2) 20 Amp Push Button / GFCI

Receptacles with Cover: (2) NEMA 5-20R Duplex

(1) NEMA L5-30R

(1) NEMA L14-30R

Receptacles without Cover: (1) CS6369 50 amp

(1) 12 VDC Charge Port

VFT Meter / Self Scrolling User Interface:

(Volts / Frequency / Hour)

**Fuel Capacity:** 9.2 Gallons / 34.8 Liters

> Fuel Type: Unleaded <10% Ethanol

Fuel Gage: Built In Tank

Run Time 50% Load: 11 Hours

> 1.9 Quart / 60.8 Ounces / 1.8 Liters Oil Capacity:

(with oil filter change)

10W-30 SAE Oil Type

(1) U Shaped Lift Bar - Included Handles:

Wheel Type: (2) 3" Wide, Solid with Bearings

Oil, Funnel, Tool Kit, 12Vdc Battery Bonus Accessories:

Charger

Warranty: 1 Year Commercial / 2 Year Residential

Steel HD 32 mm Frame Diameter:

> User Installed / Included Lifting Kit:

Grounding: **Bonded Neutral** 

### Westpro Power Systems, LLC

W237 N2889 Woodgate Road, Unit B Pewaukee, WI 53072 USA www.westpropower.com

855-944-3571

## July 2014

Model: 10KPRO

## 10KPRO Portable Generator

10000 RUNNING WATTS / 12500 STARTING WATTS

## Westinghouse **V-TWIN Engine**

Heavy duty features including: 680cc, OHV engine with pressurized lubrication system, low oil shutdown, shock mounted oil cooler, automotive type oil filter and large 9.2 gallon fuel tank



## **Full Cage Steel Frame**

Helps protect unit from damage, includes lifting kit

### **GFCI Protected Control Panel**

**Data Center** 

maintenance cycles

Simple to use controls with covered outlets for tough working conditions

Provides volts, frequency and

hours for on-site use and proper













## **Dimensions and Weights**

Unit Length:	30.7 in / 780 mm
Unit Width:	31.1 in / 790 mm Assembled
Unit Height:	31.3 in / 795 mm
Unit Weight Dry:	300 lbs / 136 kg
Carton Length:	34.6 in / 880 mm
Carton Width:	27.5 in / 700 mm
Carton Height:	33.2 in / 845 mm
Carton Weight:	310 lbs / 141 kg
UPC:	855464003568









