


# 8KPRO

## Portable Generator

Commercial / Residential

8,000 Watt Running  
10,000 Watt Starting  
Electric Start  
420cc SD Single



# Westinghouse

INNOVATION YOU CAN BE SURE OF

# Specifications

Running Watts:	8,000
Starting Watts:	10,000
Alternator:	<5% THD all Copper
Voltage Regulation:	Automatic/Remote Mounted
Displacement:	420cc
Type:	OHV, 4 stroke
Rated RPM:	3600
Lubrication:	Splash
Fuel Shut Off:	Manual/Electronic
Choke:	Automatic
Starting:	Electric/Manual
Battery:	Included, 14 Ahr
Battery Charging:	120 volt charging port/engine charging in operation
Remote Starting:	Yes
Fuel Quick Drain:	Yes
Idle Control:	Yes
Engine Protection:	Low Oil
Emission Certificaitons:	EPA/CARB
Other Certifications:	CE
Full Panel GFCI Protection:	(1) 30 amp GFCI main toggle
Secondary Breakers:	(1) 30 amp toggle (2) 20 amp Push Button/GFCI
Receptacles with Cover:	(2) NEMA 5-20R Duplex (1) NEMA L14-30R
Receptacles without Cover:	(1) L5-30R, (1) 12 Vdc charge port
Frame Diameter:	32 mm
Handles:	(1) U shaped lift bar
Lift Hook:	User Installed/Included
Wheel Type:	(2) 3" Thick Solid Fill with Bearings
Brake:	Ground Anchor/ Included
Grounding:	Bonded Neutral
User Interface:	VFT meter
Fuel Capacity:	9.2 gallons
Fuel Type:	Unleaded <10% Ethanol
Fuel Gage:	Built In Tank
Run Time 50% Load:	19
Oil Capacity:	1.0L
Bonus Accessories:	1.0L Oil, Funnel, Tool Kit, DC Battery Charger
Warranty:	1 Year Commercial / 2 Year Residential
Frame Diameter:	Steel HD 32 mm
Lifting Kit:	User Installed / Included
Grounding:	Bonded Neutral

# 8KPRO Portable Generator

8000 RUNNING WATTS / 10000 STARTING WATTS

## Westinghouse SD Engine

Heavy duty features including; OHV engine, low oil shutdown, cast iron sleeve, forged components and large 9.2 gallon fuel tank



## Full Cage Steel Frame

Helps protect unit from damage, includes lifting kit

## GFCI Protected Control Panel

Simple to use controls with covered outlets for tough working conditions




## Data Center

Provides volts, frequency and hours for on-site use and proper maintenance cycles

## Low Idle Control

Adjusts idle based on demand - lowers fuel consumption on jobsite

## Remote Start



## Dimensions and Weights

Box Length:	30.6 in / 775 mm
Box Width:	25.3 in / 645 mm
Box Height:	24.6 in / 625 mm
Weight:	238 lbs / 108 kg
UPC:	855464003728

Westpro Power Systems, LLC  
W237 N2889 Woodgate Road, Unit B  
Pewaukee, WI 53072 USA  
www.westpropower.com

855-944-3571

Model: 8KPRO  
July 2014

WESTINGHOUSE, and INNOVATION YOU CAN BE SURE OF are trademarks of Westinghouse Electric Corporation. Used under license by Westpro Power Systems, LLC. All Rights Reserved.

