

WGen3600v

3600 Watt Open Frame Gasoline Portable Generator

3600 Running Watts | 4650 Peak Watts



Rugged roll bars for added strength and protection

Fuel gauge on top of 4 gal. tank



50 State and
Canada Model

30 amp TT-30R Recreational
Vehicle Outlet


Compact design is perfect
for truck beds and tailors

Easy start yellow touch points
on choke, engine control
switch and oil fill cap

Dependable 5.9 HP 212cc OHV
4-Stroke Westinghouse engine



Pulse-Flo™ quiet muffler
with EPA & CARB
compliant emissions



What Comes in the Box



WGen3600v

Generator Specifications



Gasoline Running Watts	3600
Gasoline Peak Watts	4650
Running Amps	30 amps
Peak Amps	38 amps
AC Voltage	120 Volts
AC Frequency	60 Hz
Engine Horse Power (HP)	5.9 HP
Total Harmonic Distortion (THD)	<23%
Automatic Voltage Regulator (AVR)	Yes
Starting System	Recoil
Battery	No
Push Button Start	No
Mobile App Compatible	No
Engine Displacement	212cc
Engine Brand	Westinghouse
Engine Type	OHV 4 Stroke
Engine RPM	3600
Operational Volume (dBA)	69 dBA
Spark Plug (included)	Torch F7TC
Carburetor Kit Required to Operate at Altitude	Yes
Altitude Carburetor Kit Number (sold separate)	140544
Auto Idle Control	No
Built-in Inverter	No
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	.6 qt. (20.3 oz.)
Oil Capacity (Quarts/Ounces)	.6 qt. (20.3 oz.)
Low Oil Shutdown	Automatic
Fuel Type	Unleaded Gasoline, %10 Ethanol or less
Fuel Shut Off	Manual
Fuel Tank Material	Steel
Fuel Tank Capacity (Gallons/Liters)	4 gal. (15 L)
Run Time at %25 Load (hrs.)	18 hrs.
Run Time at %50 Load (hrs.)	13.5 hrs.
Gasoline Fuel Gauge	Yes
Choke type	Manual

Choke Location	Above Air Filter
AC Outlets	(1) 120V 30A (TT-30R) (1) 120V 30A (L5-30R) (1) 120V Duplex 20A (5-20R)
Ground	Neutral Floating
Covered Outlets	Yes
Transfer Switch Ready	No
Westinghouse Portable Transfer Switch Ready (ST Switch)	No
GFCI Outlets	No
VFT Data Center (volts, frequency, lifetime hours)	No
RV Ready Outlet	Yes
Overload Protection (circuit breaker)	Yes
Wheel Kit Included	No
Frame Thickness in. (mm)	1 in. (25 mm)
Emissions	EPA, CARB
Canada CSA Compliant	Yes
Muffler	Pulse-Flo™
Spark Arrestor	Yes
Residential Warranty	3 Years or 1000 hrs
Commercial Warranty	6 Months or 1000 hrs
Assembled Length in. (mm)	23.3 in. (590 mm)
Assembled Width in. (mm)	17.5 in. (445 mm)
Assembled Height in. (mm)	18.7 in. (475 mm)
Carton Length in. (mm)	23.9 in. (608 mm)
Carton Width in. (mm)	18.3 in. (465 mm)
Carton Height in. (mm)	19 in. (485 mm)
Dry Unit Weight lb. (kg)	99 lb. (45 kg)
Shipping Weight lb. (kg)	104 lb. (47.1 kg)
UPC	855464003599
GTIN	00855464003599

09252017KD
©2017 Westinghouse Portable Power
Specifications are subject to change without notice
Westinghouse Portable Power
777 Manor Park Dr., Columbus, OH 43228

**Have questions? Contact our team
at service@wpowerreq.com or call
855.944.3571**

