

WGen5500

5500 Watt Open Frame Gasoline Portable Generator

5500 Running Watts | 6850 Peak Watts



50 State and
Canada Model

Rugged roll bars for added
strength and protection

VFT Data Center displays volts,
frequency and lifetime hours

Single U-shaped folding
handle makes moving the
generator easy with one hand

Dependable 13 HP 420cc OHV
4-Stroke Westinghouse engine



Pulse-Flo™ quiet muffler
with EPA & CARB
compliant emissions

Fuel gauge on top of
6.6 gal. tank



What Comes in the Box



WGen5500

Generator Specifications



Gasoline Running Watts	5500
Gasoline Peak Watts	6850
Running Amps	23 amps
Peak Amps	28 amps
AC Voltage	120/240 Volts
AC Frequency	60 Hz
Engine Horse Power (HP)	13 HP
Total Harmonic Distortion (THD)	<23%
Automatic Voltage Regulator (AVR)	Yes
Starting System	Recoil
Battery	No
Push Button Start	No
Mobile App Compatible	No
Engine Displacement	420cc
Engine Brand	Westinghouse
Engine Type	OHV 4 Stroke
Engine RPM	3600
Operational Volume (dBA)	72 dBA
Spark Plug (included)	Torch F7TC
Carburetor Kit Required to Operate at Altitude	Yes
Altitude Carburetor Kit Number (sold separate)	140545
Auto Idle Control	No
Built-in Inverter	No
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	1.1 qt. (37.2 oz.)
Oil Capacity (Quarts/Ounces)	1.1 qt. (37.2 oz.)
Low Oil Shutdown	Automatic
Fuel Type	Unleaded Gasoline, %10 Ethanol or less
Fuel Shut Off	Manual
Fuel Tank Material	Steel
Fuel Tank Capacity (Gallons/Liters)	6.6 gal. (25 L)
Run Time at %25 Load (hrs.)	20 hrs.
Run Time at %50 Load (hrs.)	15 hrs.
Gasoline Fuel Gauge	Yes
Choke type	Manual

Choke Location	Above Air Filter
AC Outlets	(1) 120/240V 30A (L14-30R), (2) Duplex 120V 20A GFCI (5-20R)
Ground	Neutral Bonded
Covered Outlets	Yes
Transfer Switch Ready	Yes
Westinghouse Portable Transfer Switch Ready (ST Switch)	No
GFCI Outlets	Yes
VFT Data Center (volts, frequency, lifetime hours)	Yes
RV Ready Outlet	No
Overload Protection (circuit breaker)	Yes
Handle Style	Single Handle with Foam Grip
Wheel Kit Included	Yes
Wheel Size	10 in. Diameter, 2.5 in. Wide
Wheel Type	Polyurethane
Frame Thickness in. (mm)	1.25 in. (32 mm)
Emissions	EPA, CARB
Canada CSA Compliant	Yes
Muffler	Pulse-Flo™
Spark Arrestor	Yes
Residential Warranty	3 Years or 1000 hrs
Commercial Warranty	6 Months or 1000 hrs
Assembled Length in. (mm)	27.2 in. (690.8 mm)
Assembled Width in. (mm)	26.1 in. (662.94 mm)
Assembled Height in. (mm)	26 in. (660.4 mm)
Extended Length in. (mm)	40.7 in. (1033.9 mm)
Carton Length in. (mm)	31.1 in. (790 mm)
Carton Width in. (mm)	21.4 in. (545 mm)
Carton Height in. (mm)	23.2 in. (590 mm)
Dry Unit Weight lb. (kg)	170 lb. (77.1 kg)
Shipping Weight lb. (kg)	178 lb. (80.7 kg)
UPC	855464003971
GTIN	00855464003971

09252017KD
 ©2017 Westinghouse Portable Power
 Specifications are subject to change without notice
 Westinghouse Portable Power
 777 Manor Park Dr., Columbus, OH 43228

**Have questions? Contact our team
 at service@wpowereq.com or call
 855.944.3571**

