

P03504

CERTIFICATION // EPA, CARB, cETL



4450

STARTING WATTS
VATIOS DE ARRANQUE
WATTS AU DÉMARRAGE



3550

RUNNING W ATTS*
VATIOS DE C ONTINUO S*
WATTS DE FONCTIONNEMENT *



UPC // 840876135044

VOLTAGE // 120V

FREQUENCY // 60Hz

ENGINE TYPE // OHV

STARTING SYSTEM // RECOIL

FUEL TANK SIZE // 5.0 GAL

RUN-TIME // UP TO 14 HRS (@50% LOAD)

DECIBELS // 67 dB (@7m @50% LOAD)

CARTON L×W×H // 27.2" × 18.1" × 19.9"

CARTON WEIGHT // 117 LBS.

UNIT WEIGHT // 108.5 LBS.

UNITS PER PALLET // 16

UNITS PER CONTAINER // 320 / 40HQ

TRUCKLOAD QTY // 348

CONTROL PANEL

(2) 5-20R 20A-120V

(1) TT-30R 30A-120V RV READY

(1) L5-30R 30A-120V TWIST LOCK




14-HR



4450

STARTING WATTS



30A

120V



CARBON MONOXIDE
SHUTDOWN



ALERT SYSTEM



208
CC