

P08013

CERTIFICATION // EPA, CARB, CETL



10000

STARTING WATTS
VATIOS DE ARRANQUE
WATTS AU DÉMARRAGE



8000

RUNNING WATTS*
VATIOS DE CONTINUO S*
WATTS DE FONCTIONNEMENT *



UPC // 840876180136

VOLTAGE // 120V/240V

FREQUENCY // 60Hz

ENGINE TYPE // OHV

STARTING SYSTEM // RECOIL, ELECTRIC, REMOTE

FUEL TANK SIZE // 8.0 GAL

RUN-TIME // UP TO 12 HRS (@50% LOAD)

DECIBELS // 74 dB (@7m @50% LOAD)

CARTON L*W*H // 31.7" x 21.7" x 24.4"


CARTON WEIGHT // 233 LBS.

UNIT WEIGHT // 208 LBS.

UNITS PER PALLET // 4

TRUCKLOAD QTY // 176

3
YEAR
WARRANTY



POWER CORD (L14-30P TO 4*5-20R) AND HOLDER



REMOTE HOLDER




AVR VOLT-LOCK

CONTROL PANEL


- (1) 5-20R 20A-120V DUPLEX GFCI
- (1) L5-30R 120V 30A TWIST LOCK
- (1) L14-30R 120/240V 30A TWISTLOCK
- (1) 14-30R 120/240V 50A



REMOTE START / STOP




12-HR



10000

STARTING WATTS



CARBON MONOXIDE SHUTDOWN

ALERT SYSTEM



439
CC