

P12002

CERTIFICATION // EPA, CARB, cETL



15000

STARTING WATTS
VATIOS DE ARRANQUE
WATTS AU DÉMARRAGE



12000

RUNNING WATTS*
VATIOS DE CONTINUOS*
WATTS DE FONCTIONNEMENT *



UPC // 840876120026

VOLTAGE // 120 / 240V

FREQUENCY // 60Hz

ENGINE TYPE // OHV

STARTING SYSTEM // ELECTRIC

FUEL TANK SIZE // 13.0 GAL

RUN-TIME // UP TO 11 HRS (@50% LOAD)

DECIBELS // 81 dB (@7m @75% LOAD)

CARTON L*W*H // 42.3" x 25.6" x 35.4"

CARTON WEIGHT // 436

UNIT WEIGHT // 387

UNITS PER PALLET // 2

UNITS PER CONTAINER // 90 / 40HQ

CONTROL PANEL

(2) 5-20R 20A-120V GFCI

(1) 14-50R 50A-120/240V

(1) L14-30R 30A-120/240V TWISTLOCK

(2) L5-30R 30A-120V TWISTLOCK



CORD WRAP



IDLE CONTROL



V-TWIN POWER



4 IN 1 DATA MINDER

15000

STARTING WATTS

760 CC

CARBON MONOXIDE
SHUTDOWN



ALERT SYSTEM

11-HR



50A

120/240V