

W01785

CERTIFICATION // EPA, CARB, cETL



2100

STARTING WATTS
VATIOS DE ARRANQUE
WATTS AU DÉMARRAGE



1700

RUNNING WATTS*
VATIOS DE CONTINUO 5*
WATTS DE FONCTIONNEMENT *



UPC // 840876117859

VOLTAGE // 120V

FREQUENCY // 60Hz

ENGINE TYPE // OHV

STARTING SYSTEM // RECOIL

FUEL TANK SIZE // 0.9 GAL

RUN-TIME // UP TO 9 HRS (@25% LOAD)

DECIBELS // 54 dB (@7m @25% LOAD)

CARTON L*W*H // 21.7" x 15.0" x 18.5"

CARTON WEIGHT // 54 LBS.

UNIT WEIGHT // 45.9 LBS.

UNITS PER PALLET // 25 / 12

TRUCKLOAD QTY // 600



PARALLEL CAPABLE



LOW THD
*3%



RELIABLE RECOIL

CONTROL PANEL

(1) 5-20R 20A-120V

(1) L5-30R 30A-120V TWIST LOCK

(1) USB OUTLET 2.1A-5V



BONUS · BONUS · BONUS



PARALLEL CABLE
CABLE PARALELO
CÂBLE PARALLÈLE



ADAPTER
ADAPTADOR
ADAPTATEUR
(L5-30P TO T1-30R)



CARBON MONOXIDE
SHUTDOWN
ALERT SYSTEM



2100
STARTING WATTS



9-HR
RUN TIME



LIGHTWEIGHT



**80
CC**