

# W036630F

**4200**

STARTING WATTS  
VATIOS DE ARRANQUE  
WATTS AU DÉMARRAGE



**3650**

RUNNING WATTS\*  
VATIOS DE CONTINUO\*  
WATTS DE FONCTIONNEMENT \*

CERTIFICATION // EPA, CARB, cETL



UPC // 840876136638

VOLTAGE // 120V

FREQUENCY // 60Hz

ENGINE TYPE // OHV

STARTING SYSTEM // REMOTE / ELEC / RECOIL

FUEL TANK VOLUME // 6.0 GAL

RUN-TIME // UP TO 18 HRS (@25% LOAD)

DECIBELS // 69 dB (@7m @25% LOAD)

CARTON L×W×H // 28.7" × 21.1" × 21.3"

CARTON WEIGHT // 128 LBS.

UNIT WEIGHT // 116 LBS.

UNITS PER PALLET // 16

UNITS PER CONTAINER // 256 / 40HQ

TRUCKLOAD QTY // 336

## CONTROL PANEL

(2) 5-20R 20A-120V

(1) 14-50R 50A-120 / 240V

(NOT FOR 240V USE)

(1) L5-30R 30A-120V TWIST LOCK

(1) DC OUTLET 8.3A-12V

(1) USB OUTLET 2.1A-5V

