

WH036620F

CERTIFICATION // EPA, CARB, cETL



4500

STARTING WATTS
VATIOS DE ARRANQUE
WATTS AU DÉMARRAGE



3650

RUNNING WATTS*
VATIOS DE CONTINUO S*
WATTS DE FONCTIONNEMENT *

4100

STARTING WATTS
VATIOS DE ARRANQUE
WATTS AU DÉMARRAGE



3300

RUNNING WATTS*
VATIOS DE CONTINUO S*
WATTS DE FONCTIONNEMENT *



UPC // 840876136621

VOLTAGE // 120V

FREQUENCY // 60Hz

ENGINE TYPE // OHV

STARTING SYSTEM // ELECTRIC / RECOIL

FUEL TANK VOLUME // 6.0 GAL

RUN-TIME // UP TO 22 HRS (@25% LOAD)

DECIBELS // 64 dB (@7m @25% LOAD)

CARTON L×W×H // 28.7" × 21.1" × 21.3"

CARTON WEIGHT // 132 LBS.

UNIT WEIGHT // 119 LBS.

UNITS PER PALLET // 16

UNITS PER CONTAINER // 256 / 40HQ

TRUCKLOAD QTY // 312

CONTROL PANEL

(2) 5-20R 20A-120V

(1) 14-50R 50A-120V


(1) L5-30R 30A-120V TWIST LOCK

(1) DC OUTLET 8.3A-12V


(2) USB OUTLET 2.1A-5V



BONUS · BONUS · BONUS



HOSE HOLDER
SOPORTE DE
MANGUERA
PORTE-TUYAU



ADAPTER
ADAPTADOR
ADAPTATEUR
(L5-30P TO TT-30R)

