

GP3600

Specifications

Model (Configuration)	7677-0 (49 State) 7678-0 (50 State)
AC Rated Output Running Watts	3600
AC Maximum Output Starting Watts	4500
Rated AC Voltage	120 VAC
Rated AC Frequency	60 Hz
Rated 120 VAC Amperage	30A
Max 120 VAC Amperage	37.5
Engine Displacement	212cc
Engine Type	OHV
Engine RPM	3600
Recommended Oil	10W-30 / SAE 30
Oil Capacity qt (L)	0.63 (0.6)
Lubrication Method	Splash
Automatic Voltage Regulation (AVR)	Yes
Choke Location	On Engine
Fuel Shut Off	On Fuel Tank
Starting Method	Recoil Pull Start
Low Oil Shutdown	Yes

Neutral Bonded to Ground	No
Floating Neutral	Yes
Start Switch Type	On/Off
Start Switch Location	On Control Panel
Fuel Gauge	Yes
Fuel Tank Capacity gal (L)	3.7 (14)
Run Time at 50% (Hours)	9.3
Handle Style	Single Folding
Wheel Type	8" Never Flat
Warranty- Residential	3 Year Limited
Warranty- Commercial	1 Year Limited
Included	Engine oil, oil funnel, handle and wheel kit, and owner's manual

Dimensions and Weights

Length in (mm)	24 (610)
Width in (mm)	22.5 (570.5)
Height in (mm)	21.3 (541.5)
Extended Length in (mm)	36.5 (924)
Carton Length in (mm)	27.2 (690)
Carton Width in (mm)	17.9 (455)
Carton Height in (mm)	19.7 (500)
Unit Weight lbs (kg)	105 (47.6)
Shipping Weight lbs (kg)	112 (50.8)

