



**MORE  
POWER**



**MORE  
PRODUCTS**



**BETTER  
ROI**

# 3" TRASH WATER PUMP

- **X-Frame - Fully Wrapped, Heavy Duty 11 Gauge Steel Frame**  
Provides rugged durability and protects the hose connections from damage
- **Generac G-Force 265cc OHC Engine**  
With low-oil shutdown
- **Large 2.9 Gallon Steel Fuel Tank**  
With incorporated fuel gauge provides up to 4.3 hours of run time
- **Steel Lifting Pocket**  
Designed for easier lifting and transportation on jobsites by crane or forklift
- **Engraving Plate**  
Allows unit to be tagged /cataloged for use in contractor and rental fleets
- **Color-coded Suction and Discharge ports**  
To ensure the correct hose connections. (Blue = Discharge; Green= Suction)
- **Easy Prime**  
Custom funnel design for quick and easy priming
- **Durable Silicon Carbide Mechanical Seal**  
For long life
- **Onboard Instructions**  
With icons of key touch points make this pump easy to use



POWERED BY **GENERAC**  
**G-FORCE**

## BENEFITS

- **Built for the Jobsite:** Durable fully wrapped 11 gauge steel tube frame protects the engine and hose connections.
- **Easy Service:** Tool-free oil changes and commonly used service parts listed directly on unit.
- **Extended Runtimes:** Pump more than twice as long on one tank of fuel vs. the competition.\*

\*Compared to Honda WT30 3" Trash Pump which has a 1.5 hr max runtime at max discharge.

# 3" TRASH WATER PUMP



## SPECIFICATIONS

MODEL NAME: XC3000P

|                         |                          |                              |                   |
|-------------------------|--------------------------|------------------------------|-------------------|
| MODEL NUMBER            | G0077250<br>(50ST & CAN) | VOLUTE                       | Ductile Cast Iron |
| UPC                     | 696471079692             | HOSE KIT INCLUDED            | N/A               |
| ENGINE TYPE             | 4 cycle/OHC              | DISCHARGE HOSE LENGTH (FT/M) | N/A               |
| ENGINE DISPLACEMENT     | 265                      | SUCTION HOSE LENGTH (FT/M)   | N/A               |
| START TYPE              | Recoil Pull Start        | HOSE CONNECTIONS             | N/A               |
| LOW OIL SHUTDOWN METHOD | Low Level                | STRAINER                     | Yes               |
| RECOMMENDED OIL         | 10W-30 / SAE30           | WHEEL KIT METHOD             | N/A               |
| FUEL CAPACITY (GAL/L)   | 2.9/10.9                 | COUNTRY OF ORIGIN            | China             |
| MAX RUN TIME            | 4.3 hrs                  | WARRANTY                     | 3 Year            |
| MAX FLOW GPM/LPM        | 350/1352                 | MANUAL PART #                | 10000016160       |
| MAX TOTAL HEAD (FT/M)   | 90/27                    | LENGTH (L) (IN/MM)           | 31.5/800          |
| MAX SUCTION LIFT (FT/M) | 26/7.9                   | WIDTH (W) (IN/MM)            | 23.5/597          |
| MECHANICAL SEAL TYPE    | Silicon Carbide          | HEIGHT (H) (IN/MM)           | 29.25/743         |
| SOLID HANDLING (IN)     | 1.2                      | UNIT WEIGHT (LBS/KG)         | 163/74            |
| SUCTION PORT (NPT)      | 3                        | CARTON LENGTH (IN/MM)        | 32.2/817          |
| DISCHARGE PORT (NPT)    | 3                        | CARTON WIDTH (IN/MM)         | 24.1/612          |
| PUMP HOUSING            | Aluminum                 | CARTON HEIGHT (IN/MM)        | 25.3/642          |
| IMPELLER                | Ductile Cast Iron        | SHIPPING WEIGHT (LBS/KG)     | 173/78.5          |

**GENERAC**  
PRO



**DURABLE, RUGGED  
PRODUCT DESIGN**



**THREE YEAR  
LIMITED WARRANTY**



**24/7 • 365  
CUSTOMER CARE**