

iGen1200

1200 Watt Digital Inverter Gasoline Portable Generator

1000 Running Watts | 1200 Peak Watts



Built-in carry handle
for easy transportation

Fuel efficient, .8 gallon fuel tank
that runs 9 hrs at 25% load

Simple access panel for
easy maintenance

Two 5V USB ports for charging
sensitive electronics such as
phones or tablets

Rubber outlet dust covers



Dependable 1.8 HP 54cc OHV
4-Stroke Westinghouse engine



Double-insulated acoustic
enclosure and low tone mufflers
to reduce operating noise



Parallel capable with another
iGen using WHPC (additional
generator and WHPC cord
sold separately)

<3% THD
SINE WAVE OUTPUT

120V AC POWER
OUTLETS WITH
DUST COVER

LOW OIL,
OVERLOAD &
OUTPUT READY
LIGHTS

DUAL USB
PORTS WITH
DUST COVER

EFFICIENCY
MODE

CIRCUIT
BREAKER

GROUND

What Comes in the Box



iGen1200

Inverter Generator Specifications



Gasoline Peak Watts	1200
Gasoline Running Watts	1000
Peak Amps at 120V	10 amps
Running Amps at 120V	8.3 amps
AC Voltage	120 Volts
DC Voltage	5 Volts
AC Frequency	60 Hz
Parallel Capable with WHPC cord (sold separate)	Yes
Engine Horse Power (HP)	1.8 HP
Total Harmonic Distortion (THD)	<3%
Automatic Voltage Regulator (AVR)	Yes
Starting System	Recoil
Battery	No
Engine Displacement	54cc
Engine Brand	Westinghouse
Engine Type	OHV 4 Stroke
Engine Speed	Variable
Engine RPM	Max 5200
Available in True Timber Camo	Yes
Operational Volume at 25% Load	52 dBA
Operational Volume at 50% Load	58 dBA
Spark Plug (included)	Torch A5RTC
Carburetor Kit Required to Operate at Altitude	Yes
Economy Mode Switch	Yes
Built-in Inverter	Yes
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	.37 qt. (11.8 oz.)
Oil Capacity (Quarts/Ounces)	.37 qt. (11.8 oz.)
Low Oil Shutdown	Automatic
Fuel Type	Unleaded Gasoline, 10% Ethanol or less
Fuel Shut Off	Manual
Fuel Tank Material	Plastic
Fuel Tank Capacity (Gallons/Liters)	.8 gal. (3 L)

Run Time at %25 Load (hrs.)	9 hrs.
Run Time at %50 Load (hrs.)	7 hrs.
Gasoline Fuel Gauge	No
Choke type	Manual
Choke Location	Side Panel
AC Outlets	(1) Duplex 120V 20A (5-20R)
DC Outlets	(2) 5V USB ports
Ground	Floating Neutral
Covered Outlets	Yes
Transfer Switch Ready	No
Westinghouse Portable Transfer Switch Ready (ST Switch)	No
Voltmeter	No
GFCI Outlets	No
LED Data Center	No
RV Ready Outlet	No
Overload Protection (circuit breaker)	Yes
Handle Style	Single, molded in case
Wheel Kit	No
Emissions	EPA, CARB
Canada CSA Compliant	No
Muffler	Pulse-Flo™
Spark Arrestor	Yes
Residential Warranty	3 Years or 1000 hrs.
Commercial Warranty	6 Months or 1000 hrs.
Assembled Length in. (mm)	18 in. (457 mm)
Assembled Width in. (mm)	8.5 in. (216 mm)
Assembled Height in. (mm)	15.5 in. (394 mm)
Carton Length in. (mm)	18.5 in. (470 mm)
Carton Width in. (mm)	11.2 in. (285 mm)
Carton Height in. (mm)	15.7 in. (400 mm)
Dry Unit Weight lb. (kg)	33 lb. (15 kg)
Shipping Weight lb. (kg)	36.3 lb. (16.5 kg)
UPC	855464003872
GTIN	00855464003872

09222017K_NCSA
 ©2017 Westinghouse Portable Power
 Specifications are subject to change without notice
 Westinghouse Portable Power
 777 Manor Park Dr., Columbus, OH 43228

**Have questions? Contact our team
 at service@wpowereq.com or call
 855.944.3571**



/wpowereq



/WestinghouseProducts



WestinghousePortablePower.com

