



DP3000HR 2,500 RUNNING WATTS



Honda GX160 Engine



Brushless Industrial Genend_o with clean power



An American Company 🖕

We produce our products in our 200,000ft² facility located in Le Center, Minnesota, equipped with modern engineering, fabrication and assembly capabilities.







LED Display Hours, RPMs, voltage, and frequency readings automatically cycle on the display.

Load Bars

Easily verify the load balance on each leg of the generator end.

Warnings

The LED will flash if any parameter gets outside of normal range. A warning will also be displayed when it is time for an oil change.



SPECIFICATIONS

ENGINE

ENGINE BRAND	HONDA
ENGINE MODEL	GX160
ENGINE STARTER	RECOIL
ENGINE SPEED	3600 RPM
ENGINE CYLINDERS	SINGLE
DISPLACEMENT/TYPE	160 CC / OHV
FREQUENCY REGULATION ⁽¹⁾	+/- 3%
LOW OIL PROTECTION	STANDARD
RECOMMENDED OIL ⁽²⁾	10W-30
OIL CAPACITY	0.6 QT
FUEL TANK	1 GAL
FUEL GAUGE	NOT AVAILABLE
FULL LOAD RUN TIME ⁽³⁾	2.2 HOURS
FUEL CONSUMPTION 100%	GAL/HR 0.45
75%	0.37
50%	0.29
25%	0.21

NOTES: (1) Steady state frequency regulation. (2) The recommended oil is for normal applications. See operator's manual for the recommended oil for your needs. (3) Run time is estimated.

SHIPPING

<u>51 m 1 m 4 G</u>	0
SHIPPING DIMENSIONS (L x W x H)	23.5″ x 17″ x 17″
SHIP WEIGHT	104 LBS
FREIGHT CLASS	70

ELECTRICAL

	~
STARTING WATTS	3,000
RUNNING WATTS	2,500
RUNNING AMPS @ 120 VAC	20.8
VOLTAGE REGULATION	CAPACITOR +/- 5%
MAIN CIRCUIT BREAKER	20 AMP
BONDED NEUTRAL	YES
120 VOLT RECEPTACLES (GFCI)	(1) NEMA 5-20 20A DUPLEX
YOURGEN METER	STANDARD

DP3000HR

	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~
MOTOR STARTING (CODE G)	1 HP
DBA @ 7 METERS	74
TOTAL HARMONIC DISTORTION	< 1%
LIFTING EYE	NOT AVAILABLE
INSULATION	CLASS H
PROTECTIVE ROLL FRAME	1.25" DIA. 14 GA. STEEL
ASSEMBLED IN	USA
EPA APPROVED	YES
CARB APPROVED	YES
TÜV CERTIFICATION	CSA
UNIT WARRANTY ⁽¹⁾	3 YEARS
NOTES (1) E	

NOTES: (1) For more warranty information, see operator's manual.

OPTIONAL	ACCESSORIES
GENERATOR COVER	29.5″ x 22″ x 22″



23.5"



16.5"

Specifications are subject to change without notice.